

SAFETY DATA SHEET - CALIBRATION CHECK GAS

PRODUCT: ≤20%CARBON DIOXIDE/≥5%METHANE/≤6%OXYGEN/BALANCE N2 **PAGE:** 1/3
SDS NO: 019C **Version:** 2 **Date:** 30th October 2008

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

SDS NO: 019C
 Product Name: Carbon Dioxide/Methane/Oxygen Balance Nitrogen in Cylinders (≥ 17 litres)
 Company Identification: See heading and/or footer

2. HAZARDS IDENTIFICATION

Hazards identification: In high concentrations may cause asphyxiation
 Flammable gas
 Compressed gas

3. COMPOSITION/INFORMATION OF INGREDIENTS

Substance/Preparation: Preparation
 Composition/Impurities: Contains no other components or impurities, which will influence the classification of the product

4. FIRST AID MEASURES

Inhalation: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim is not aware of asphyxiation. Remove victim to uncontaminated area wearing a self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
 Ingestion: Ingestion is not considered a potential route of exposure.

5. FIRE-FIGHTING MEASURES

Fire-fighting measures: These containers hold gas under pressure, with no liquid phase. If involved in a major fire, they should be sprayed with water to avoid pressure increases, otherwise pressures will rise and ultimately they may distort or burst to release the contents. The gases will not add significantly to the fire, but containers or fragments may be projected considerable distances - thereby hampering fire-fighting efforts.

6. ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: In terms of weight, these containers hold very little contents, such that any accidental release by puncturing etc. will be of no practical concern.

SAFETY DATA SHEET - CALIBRATION CHECK GAS

PRODUCT: $\leq 20\%$ CARBON DIOXIDE/ $\geq 5\%$ METHANE/ $\leq 6\%$ OXYGEN/BALANCE N2 **PAGE:** 2/3
SDS NO: 019C **Version:** 2 **Date:** 30th October 2008

7. HANDLING AND STORAGE

Handling and Storage Suck back of water into the container must be prevented. Do not allow back feed into the container. Use only properly specified equipment, which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.

Cylinders should be stored upright and it is good practice to keep inert, flammables and oxidants apart. All cylinders should be stored with the regulator detached, this provides a very useful safety measure as it prevents accidental high pressure gas discharge. Store either outside or in a well ventilated area, away from ignition sources, ideally in a secure storage area.

High temperatures will cause the gas to expand resulting in a rise in pressure, the upper recommended limit is 45°C or 50°C, however, there is a large safety margin on the burst pressure. Mtech guarantees all mixtures to 0°C.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal protection Ensure adequate ventilation
 Carbon Dioxide WEL = 5000ppm (8hr TWA) 15000ppm (15min TWA)
 No WEL data available for Methane and Oxygen

9. PHYSICAL AND CHEMICAL PROPERTIES

Relative density, gas Similar to air at low concentrations, heavier than air at higher concentrations

Solubility mg/l water Not known, but considered to have low solubility

Appearance/Colour Colourless gas

Odour None (Hence no warning odour)

10. STABILITY AND REACTIVITY

Stability and reactivity Stable under normal conditions
 Flammable gas

11. TOXICOLOGICAL INFORMATION

General At high concentrations this may cause asphyxiation

12. ECOLOGICAL INFORMATION

General No ecological damage caused by this product.

SAFETY DATA SHEET - CALIBRATION CHECK GAS

PRODUCT: ≤20%CARBON DIOXIDE/≥5%METHANE/≤6%OXYGEN/BALANCE N2 **PAGE:** 3/3
SDS NO: 019C **Version:** 2 **Date:** 30th October 2008

13. DISPOSAL INFORMATION

Disposal Used containers are acceptable for disposal in the normal waste stream. A recycle tool is available from Mtech to enable a used non-refillable cylinder to be punctured and safely disposed of.

14. TRANSPORT INFORMATION

Land transport ADR/RID
 Sea transport IMDG
 Air transport ICAO/IATA

UN number:	UN1954
Proper Shipping Name:	Compressed gas n.o.s. (contains Carbon Dioxide, Methane, Oxygen, Nitrogen)
Class:	2 (ADR) 2.1 (IATA/IMDG)
ADR classification code:	1F
Packing Group:	N/A
Marine Pollutant:	N/A

15. REGULATORY INFORMATION

Regulatory Information Following the HSE Approved Supply List (L142) and the UK's CHIP (as currently amended) Regulations -
 Mixtures of ≥5% Methane are classified as flammable.

16. OTHER INFORMATION

Mixtures containing ≥5% Methane

R12	Extremely flammable
S(2)	Keep out of reach of children
S9	Keep container in a well ventilated place.
S16	Keep away from sources of ignition – No smoking
S33	Take precautionary measures against static discharges..

This SDS has been prepared in accordance with the Chemicals (Hazard Information and Packaging for Supply Regulation (as currently amended). The information is based on the best knowledge of Mtech and its advisors and is given in good faith, but we cannot guarantee its accuracy, reliability or completeness and therefore disclaim any liability for loss or damage arising out of use of this data. Since conditions of use are outside the control of the Company and its advisors we disclaim any liability for loss or damage when the product is used for other purposes than it is intended.