



Molenstraat 84  
B-2640 Mortsel  
M +32 (0)474 67 18 82  
F +32 (0)3 457 77 17  
info@mtechgas.be

[www.mtechgas.be](http://www.mtechgas.be)

## HPC SS Regulator

<b>Valve:</b>	<b>Pressure Regulator complete with pressure gauge and constant flow outlet of 0.3, 0.5 or 1.0 litre/minute (1.5, 2.0 or 2.5 l/min are available) Stainless steel for use with very reactive gas type. (CL2, HCL, NO2)</b>
<b>Primary use:</b>	<b>These regulators are single stage, piston type and are used with 34, 58 and 110 litre cylinders. They offer a cost effective and convenient method of gas regulation.</b>
<b>Max inlet pressure:</b>	<b>120 bar (1760 psig)</b>
<b>Valve inlet:</b>	<b>5/8" – 18 UNF (C10) male</b>
<b>Outlet:</b>	<b>6.2mm (1/4") barb</b>
<b>Flow:</b>	<b>0.15, 0.3, 0.5 or 1.0 l/min (please specify requirement)</b>
<b>Construction:</b>	<b>Body : nickel plated brass Valve seal : Viton O-ring : Viton</b>
<b>Gauge:</b>	<b>0-1000 psig (68 bar)</b>
<b>Part number:</b>	<b>HPC SS</b>

