









Overzicht Flowmeters

Type	Discription	To use with	Part number	Cylinder Type			
				20L	34L	58L	110L
	MiniFlow with flow meter 0,5-1,5l/min (also available 1,5-2,5l/min)	Non-reactive and reactive mixtures	MiniFlow1	V			
			MiniFlow2		V	V	V
	HPC controller with constant flow outlet 0,3- 0,5-1,0l/min (also 1,5- 2,0-2,5l/min)	Non-reactive and reactive mixtures	HPC		V	V	V
	HPC SS controller with constant flow outlet 0,3- 0,5-1,0l/min (also 1,5-2,0-2,5l/min)	High reactive mixtures	HPC SS		V	V	V
	A twin stage demand flow regulator	Non-reactive and reactive mixtures	Demand Flow		V	V	V
	Balance flow valve to use with gas monitors fitted with pumps	Non-reactive and reactive mixtures	BalFlow1	V			
			BalFlow2		V	V	V
	Dual purpose regulator	Non-reactive and reactive mixtures	DuoFlow		V	V	V
	S Flow regulator with integrated pressure gauge and flow meter	Non-reactive and reactive mixtures	SFlow 1	V			
	S Flow regulator with integrated pressure gauge and flow meter	Non-reactive and reactive mixtures	SFlow 2		V	V	V